

K4EGDP05VV

ELECTRIC DIRECT GRILL 1/2 MODULE + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **heating elements with AISI 304 sheath**, which work in air and are suitable for the temperatures to which they are exposed (400°C). The heat load of the heating elements allows **heat exchange only towards the food** to improve cooking and energy savings. Safety thermostat with automatic reset to protect the heating elements. Energy regulator adjusting the frequency of ON-OFF operation of the heating elements. The maximum continuous operation position is useful in the cleaning process, as it induces pyrolysis of the fats on the heating elements.

AISI 304 cold-pressed water tank with drain hole. The water improves the quality of the food cooked and carries the cooking fats to the drain.

Tap for filling and refilling water placed on the frontal panel. **Tank drain** placed on the frontal panel and operated by a lever.

2 mm thick moulded AISI 304 stainless steel worktop with rounded edges for easy cleaning. Stainless steel front, side and back panels.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm
Depth: 900 mm
Height: 850 mm
Weight: 55 kg
Volume: 0.56 m³
Electrical power: 5.40 kW

