

K7ECI05VV

INDUCTION RANGE 2 PLATES + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

6 mm-thick pyroceram work top. **27 x 27 cm square radiating areas** that are placed under glass and work thanks to a potentiometer with 9 power levels. Continuous power control. Provided with a **display placed under glass**, so you can check the set power level and see error messages (if any). Safety ensured by a sensor against overtemperature in case of functioning with empty pots. Pot detection sensor. Detection sensor of pots with a smaller diameter than 12 cm.

AISI 304 work surface with rounded corners for easy cleaning. Stainless steel AISI 304 front panel.

Possibility to work with **any kind of pots suitable for induction**: made of iron, cast iron or other ferromagnetic material. Constant energy efficiency, even if utensils of different shapes are used.

Remarkable time and power savings because of **halved cooking time and energy consumption** against traditional cooking systems. Better work environment because of lower heat losses.

Increased users' safety: only pots become hot while cooktop remains cold, so that the possibility to get burned is strongly reduced.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm
Depth: 700 mm
Height: 850 mm
Weight: 38 kg
Volume: 0.45 m³
Electrical power: 10.00 kW

